



© 1995-2018 by Isidoro Martínez

PROPERTIES OF LIQUIDS

Function values at 100 kPa and 288 K for room-temperature liquids, or at 100 kPa and the normal boiling point for room-temperature gases, or the normal melting point for room-temperature solids, or the triple point for sublimating substances (C₂H₂, CO₂, SF₈ and UF₈).

Substance	Formula	Melting temp. T_f K	Boiling temp. T_b K	Melting enthalpy h_{sl} kJ/kg	Boiling enthalpy h_{lv} kJ/kg	Density (mass) ρ kg/m ³	Thermal expansion $\alpha \cdot 10^6$ K ⁻¹	Compressibility ^a $\kappa \cdot 10^9$ Pa ⁻¹	Surface tension ^b σ N/m	Thermal capacity c_p J/(kg·K)	Thermal conductivity k W/(m·K)	Dynamic viscosity $\mu \cdot 10^6$ Pa·s
Acetylene	C ₂ H ₂	193 ^c	193 ^c	115 ^c	700 ^c	615 ^c	2500		0.001	3000	0.50	160
Acetone	C ₃ H ₆ O	178	329	98	532	749	1400	1.2	0.024	2150	0.18	330
Argon	Ar	84	87	30	163	1395	4700	2.1	0.014	625	0.13	240
Ammonia	NH ₃	195	240	332	1357	697	2400	0.71	0.022	4600	0.50	266
Aniline	C ₆ H ₇ N	276	457	114	434	1021	840	0.36	0.042	2140	0.17	4467
1,3-Butadiene	C ₄ H ₆	164	269	148		621	1800		0.013	2260	0.13	
Benzene	C ₆ H ₆	279	353	126	394	884	1200	0.97	0.029	1720	0.15	653
n-Butane	C ₄ H ₁₀	135	273	80	365	602 ^d	1800	1.9	0.012	2400	0.12	282
iso-Butane	C ₄ H ₁₀	115	261	78	366	594 ^e	2000	2.3	0.012	2300	0.12	150
Carbon dioxide	CO ₂	217 ^f	217 ^f	185 ^f	350 ^f	1180 ^f	3100 ^f	0.88 ^f	0.017 ^f	1950 ^f	0.18 ^f	260 ^f
Carbon tetrachloride	CCl ₄	250	350	30	195	1590	1240	1.0	0.027	840	0.11	967
Cyclohexane	C ₆ H ₁₂	280	354	31	360	778	1430	0.72	0.025	1860	0.13	411
Chloroform	CHCl ₃	210	335	74	247	1489	1200	0.69	0.027	980	0.13	562
n-Decane	C ₁₀ H ₂₂	243	447	202	276	730	1010	0.84	0.024	2000	0.15	920
Diesel	(C ₁₂ H ₂₆)	235 ^g	470 ^g		250	840	830		0.028	1900	0.15	2400
1-Dodecene	C ₁₂ H ₂₄	238	586	122	373	761	980			2150	0.14	1360
n-Dodecane	C ₁₂ H ₂₆	263	489	216	257	780	920	0.77	0.025	2220	0.14	1340
DME (dimethyl ether)	C ₂ H ₆ O	132	250	107	460	736	4850	1.8	0.011	2540	0.14	100

ETBE (ethyl tert-butyl ether)	$C_6H_{14}O$	179	340			770						400
Ethane	C_2H_6	90	185	95	520	544 ^h	2310 ^h	1.1 ^h	0.016 ^h	2440 ^h	0.17 ^h	169 ^h
Ethanol	C_2H_6O	156	351	108	860	790	1100	1.1	0.023	2440	0.18	1194
Ether (diethyl ether)	$C_4H_{10}O$	157	308	99	351	715	1630		0.016	2260	0.14	230
Ethylene glycol	$C_2H_6O_2$	262	471	181	800	1110	650	0.33	0.048	2400	0.26	20000
Ethylene	C_2H_4	104	169	120	483	568 ⁱ	2530	1.0	0.016	2420	0.19	176
Gasoline	(C_8H_{18})	217 ^g	360 ^g		340	750	900		0.025	2100	0.15	380
Glycerol (glycerine)	$C_3H_8O_3$	291	560	199	663	1260	500	0.21	0.064	2430	0.30	1400000
Helium (4He)	He	0.95	4.2	3.5	20.7	125	200 000	520	0.0001	5000	0.02	3.2
Helium-3 (3He)	He	NA	3.2	NA	8.7	59	50 000	300		1500		
n-Heptane	C_7H_{16}	182	372	140	321	684	1220	1.1	0.020	2220	0.13	409
n-Hexane	C_6H_{14}	178	342	150	337	658	1200	1.3	0.019	2260	0.12	320
n-Hexadecane (cetane)	$C_{16}H_{34}$	291	550	230	358	773			0.028	2210	0.15	3030
Hydrazine	N_2H_4	275	387	395	1400	1010	2090	0.22	0.067	3080	0.57	900
Hydrogen ⁱ	H_2	14	20	59	448	71	64 000	9.07	0.002	8700	0.12	10
(Hydrogen) Deuterium	D_2	19	23	49	304	163	16 800	13.3		8000	0.14	
Kerosene, Jet A-1, RP1	$(C_{12}H_{24})$	230 ^g	450 ^g		250	820	830	0.70	0.028	2000	0.13	2400
Mercury	Hg	234	630	12	301	13546	180	0.038	0.490	139	9.3	1550
Methane	CH_4	91	112	58	511	423	3480	1.17	0.012	3420	0.18	110
Methanol	CH_4O	175	338	99	1100	791	1490	1.05	0.023	2510	0.21	593
MMH (monomethyl hydrazine)	CH_6N_2	221	364			875				2950	0.25	
MTBE (methyl tert-butyl ether)	$C_5H_{12}O$	164	328	88		740				2090	0.12	350
Nitric acid	HNO_3	231	394	167	615	1510		0.32	0.042	2000	0.29	800
Nitrogen	N_2	63	77	26	199	807	5600	3.2	0.012	2040	0.145	161
di-Nitrogen oxide	N_2O	182	185	149	376	1230	6000	0.63	0.024	1720	0.20	325
di-Nitrogen tetroxide ^j	N_2O_4	262	294	160	330	1440				1550	0.29	
n-Octane	C_8H_{18}	217	399	181	306	703	1060	0.98	0.022	2100	0.15	562

iso-Octane	C ₈ H ₁₈	166	372	180	308	692			0.018	2100	0.10	350
Oil (mineral, vegetable...) ^k	C ₁₈ H ₃₆ O ₂					900	900	0.51		2000	0.15	10 ³ ..10 ⁷
Oxygen	O ₂	54	90	14	213	1142	12 000	0.79	0.020	1700	0.15	
n-Pentane	C ₅ H ₁₂	143	309	116	356	626	1500	1.4	0.016	2180	0.14	229
Propane ^l	C ₃ H ₈	85	231	95	430	581	4900	1.3	0.016	2140	0.13	198 ^j
Propylene (propene)	C ₃ H ₆	88	225	71	437	612	2100	3.2	0.008	2200	0.11	190
Propylene glycol	C ₃ H ₈ O ₂	214	461	99		1036	730			2790	0.20	
R12 ^m	CCl ₂ F ₂	115	243		165	1488	1970	2.5	0.016	966	0.07	200
R134a (tetrafluoroethane) ⁿ	CF ₃ CH ₂ F	177	247	1300	215	1380	2190	1.3	0.015	1280	0.10	380
R410A ^o	n.a.	120	222		190	1350	2190	1.7	0.018	1368	0.17	
Silicone oil DMS-10	-[Si(CH ₃) ₂ O]-			1050		950	900	0.6	0.021	1800	0.11	9500
Sodium ^p	Na	371	1160	115	1020	780 ^p	70	0.20	0.200	1250	60	200
Sulfur dioxide	SO ₂	198	263	135	389	1455	1800	0.98			0.20	550
Sulfur hexafluoride ^q	SF ₆	223	223	40	162	1845	2700	11	0.011	837		
Sulfuric acid	H ₂ SO ₄	283	561		745	1840		0.3		1400		23000
Tetradecafluorohexane ^r (FC-72)	C ₆ F ₁₄	183	329		88	1680	1560		0.010	1100	0.057	640
UDMH (unsym.dim.hydrazine)	C ₂ H ₈ N ₂	216	337			790				2650	0.16	
Uranium hexafluoride ^s	UF ₆	337	337	54	82	3670	6000		0.018	620	1.9	900
Water ^t	H ₂ O	273	373	334	2257	999	150	0.45	0.073 ^t	4180	0.60	1000 ^t
Water, Heavy ^u	D ₂ O	277	374	319	2090	1105	100	0.47	0.073	4210	0.60	
Xenon	Xe	161	165	17	96	2990	2300	3.55	0.018	350	0.07	450

a) The compressibility coefficient, κ , is related to the speed of sound, c , and the density by $c=(\rho\kappa)^{-1/2}$ (e.g. for pure water $c=(\rho\kappa)^{-1/2}=(998\cdot 0.46\cdot 10^{-9})^{-1/2}=1480$ m/s; and roughly the same for sea water).

b) Surface tension for liquid in air. For liquid in water (if immiscible, of course), values may differ (e.g. for benzene in air $\sigma=0.029$ N/m but $\sigma=0.035$ N/m for benzene in water).

c) Acetylene has no normal points for melting and boiling because at the normal pressure of 100 kPa the only phase change is the solid-gas transition at 189 K (normal sublimation point). Data in this table refers to the triple point: $p_{tr}=128$ kPa, $T_{tr}=193$ K= -80 °C; i.e., $\rho_{l,tr}=615$ kg/m³, $h_{sv}=h_{sl}+h_{lv}=115+700=815$ kJ/kg. Sublimation point data: $T=189$ K= -84 °C, $\rho_s=729$ kg/m³, $h_{sv}=820$ kJ/kg. See additional comments in f).

d) n-Butane liquid density at 288 K and its equilibrium pressure (175 kPa): $\rho_l=584$ kg/m³.

- e) iso-Butane liquid density at 288 K and its equilibrium pressure (258 kPa): $\rho_l=563 \text{ kg/m}^3$.
- f) Carbon dioxide has no normal points for melting and boiling because at the normal pressure of 100 kPa the only phase change is the solid-gas transition at 195 K (normal sublimation point). Data in this table refers to the triple point: $p_{tr}=518 \text{ kPa}$, $T_{tr}=217 \text{ K}=-56.3 \text{ }^\circ\text{C}$; i.e., $\rho_{l,tr}=615 \text{ kg/m}^3$, $h_{sv}=h_{sl}+h_{lv}=185+350=535 \text{ kJ/kg}$. Sublimation point data: $T=195 \text{ K}=-78.5 \text{ }^\circ\text{C}$, $\rho_s=1560 \text{ kg/m}^3$ (if well compacted), $h_{sv}=575 \text{ kJ/kg}$. Notice that most liquid properties vary a lot near the critical point, which is the case at room temperature for CO_2 , C_2H_2 , C_2H_4 , C_2H_6 , N_2O , SF_6 , and UF_6 . For liquid CO_2 at 288 K and its equilibrium pressure (5.1 MPa): $\rho=823 \text{ kg/m}^3$, $\alpha=3200 \cdot 10^{-6} \text{ K}^{-1}$, $\kappa=7.8 \cdot 10^{-9} \text{ Pa}^{-1}$, $\sigma=0.002 \text{ N/m}$, $k=0.09 \text{ W/(m}\cdot\text{K)}$, and $\mu=70 \cdot 10^{-6} \text{ Pa}\cdot\text{s}$, and $c_p=3420 \text{ J/(kg}\cdot\text{K)}$, growing from $c_p=1950 \text{ J/(kg}\cdot\text{K)}$ at the triple point, to infinity at the critical point (the difference between c_p and c_v of the saturated liquid is important in this case: the thermal capacity at constant volume at 288 K and 5.1 MPa is $c_v=990 \text{ J/(kg}\cdot\text{K)}$).
- g) Diesel, gasoline and kerosene are mixtures of various compositions and have not precise boiling or melting points (e.g. at 300 K 10% wt of gasoline is in the vapour state, and at 440 K 90%). Surface tension may vary in the range $\sigma=0.022..0.035 \text{ N/m}$. [Jet A-1](#) is a kerosene fuel with additives to freeze at $-50 \text{ }^\circ\text{C}$ and $\rho=800..820 \text{ kg/m}^3$, $c=2000..2100 \text{ J/(kg}\cdot\text{K)}$, $k=0.10..0.14 \text{ W/(m}\cdot\text{K)}$). Rocket propellant [RP1](#) is similar to Jet A-1. Surrogate pure components are often used for theoretical studies, but only a few properties can be properly matched: octane (normal or iso) is used as surrogate of gasoline, and dodecane or dodecene for diesel, kerosene, Jet A-1 and RP1.
- h) Liquid ethane at 288 K and its equilibrium pressure (3.36 MPa) has $\rho_l=358 \text{ kg/m}^3$, $\alpha=0.013 \text{ K}^{-1}$, $c=430 \text{ m/s}$, $c_p=4750 \text{ J/(kg}\cdot\text{K)}$, $k=0.079 \text{ W/(m}\cdot\text{K)}$, and $\mu=45 \cdot 10^{-6} \text{ Pa}\cdot\text{s}$.
- i) There are two [spin-isomers of \$\text{H}_2\$](#) : ortho and para. Gas at room temperature is mostly orthohydrogen, but, when liquefied, it is important to convert it to almost pure parahydrogen because otherwise there is a slow natural conversion of ortho to para with a release of 516 kJ/kg that contributes to boil-off.
- j) At equilibrium, there is always a mixture of dinitrogen tetroxide (N_2O_4) and nitrogen dioxide (NO_2). The $\text{NO}_2/\text{N}_2\text{O}_4$ equilibrium depends on temperature, NO_2 being favoured in the gas phase at high temperatures, whereas N_2O_4 is preponderant in the gas phase at low temperature, and in condensed phases. When condensing, at $21.3 \text{ }^\circ\text{C}$ at 100 kPa, most of the liquid is N_2O_4 which is colourless or pale brownish; when solidified (at $-11.2 \text{ }^\circ\text{C}$) a white solid appears. N_2O_4 is a hypergolic propellant that spontaneously reacts upon contact with various forms of hydrazine, all of them liquid at normal pressure; this fact, and the ease of liquefying the N_2O_4 (liquid at 100 kPa for $T < 21 \text{ }^\circ\text{C}$), makes them popular bipropellants for spacecraft rockets.
- k) Formula of oleic acid ($\text{CH}_3-(\text{CH}_2)_7-\text{CH}=\text{CH}-(\text{CH}_2)_7-\text{COOH}$, $T_m=268 \text{ K}$, $h_{sl}=75 \text{ kJ/kg}$), the major component in olive oil. Oils are thick liquids (non-volatile and viscous) made directly (natural oils) or indirectly (synthetic oils) from fossil matter, living matter, or minerals. Mineral oils are high hydrocarbons obtained from petroleum distillation and used either as fuels (diesel oil and heavy fuel oil) or as lubricants (lube oils). Fat oils are triglycerides-esters from plants or animals (olive, soybean, peanut sunflower, coconut, corn linseed, palm, essential oils, whale, castor). They are organic (carbon) or inorganic (silicon) polymers with a range of molar mass values, and do not show sharp phase transitions. Density: they are usually less dense than water (but sulphuric oleum nearly reaches a density double than water): e.g. olive and vegetable oils have some $\rho=915..925 \text{ kg/m}^3$, whereas lubricant, combustible and hydraulic oils may have $\rho=800..1000 \text{ kg/m}^3$. Thermal capacity: values are near $c_p=2000 \text{ J/kg}\cdot\text{K}$ in most cases; lube oils have about $1800 \text{ J/kg}\cdot\text{K}$ at 250 K, linearly increasing to about $3000 \text{ J/kg}\cdot\text{K}$ at 600 K; oils use for heat transfer may have values some $200 \text{ J/kg}\cdot\text{K}$ lower. Thermal conductivity: all of them are poor conductors, with $k=0.10..0.15 \text{ W/m}\cdot\text{K}$, slightly decreasing with temperature, even for thermal oils, which are just more resistant to high temperatures (up to 600 K). Viscosity: oil viscosity may vary orders of magnitude from one oil to the other, and decreases exponentially with temperature; e.g. at $15 \text{ }^\circ\text{C}$, $\mu=3 \cdot 10^{-3} \text{ Pa}\cdot\text{s}$ for light silicone oils, gas oil and diesel oil, $\mu=80 \cdot 10^{-3} \text{ Pa}\cdot\text{s}$ for olive oil and light mineral oils, $\mu > 1000 \cdot 10^{-3} \text{ Pa}\cdot\text{s}$ for fuel oil and thick silicone oils).
- l) Liquid propane at 288 K and its equilibrium pressure (729 kPa) has $\rho_l=508 \text{ kg/m}^3$, $\alpha=2990 \cdot 10^{-6} \text{ K}^{-1}$, $c=780 \text{ m/s}$, $c_p=2620 \text{ J/(kg}\cdot\text{K)}$, $k=0.099 \text{ W/(m}\cdot\text{K)}$, and $\mu=108 \cdot 10^{-6} \text{ Pa}\cdot\text{s}$.
- m) R12, dichlorodifluoromethane (also named freon), was the most used refrigerant in the 20th c. since its first synthesis in 1929 to its production banning in 1995. Liquid R12 at 288 K and its equilibrium pressure (488 kPa) has $\rho_l=1350 \text{ kg/m}^3$, $\alpha=2600 \cdot 10^{-6} \text{ K}^{-1}$, $c=553 \text{ m/s}$, $\sigma=0.010 \text{ N/m}$, $c_p=964 \text{ J/(kg}\cdot\text{K)}$, $k=0.087 \text{ W/(m}\cdot\text{K)}$, and $\mu=343 \cdot 10^{-6} \text{ Pa}\cdot\text{s}$.
- n) Liquid R134a at 288 K and its equilibrium pressure (486 kPa) has $\rho_l=1244 \text{ kg/m}^3$, $\alpha=2920 \cdot 10^{-6} \text{ K}^{-1}$, $c=553 \text{ m/s}$, $\sigma=0.010 \text{ N/m}$, $c_p=1390 \text{ J/(kg}\cdot\text{K)}$, $k=0.085 \text{ W/(m}\cdot\text{K)}$, and $\mu=221 \cdot 10^{-6} \text{ Pa}\cdot\text{s}$.

- o) R410A is a near-azeotropic mixture of R32 (difluoromethane, CH_2F_2) and R125 (pentafluoroethane, CHF_2CF_3), 50/50 by weight (70/30 molar), which can be approximated as a pure substance. Liquid R410A at 288 K and its equilibrium pressure (1253 kPa) has $\rho_l=1107 \text{ kg/m}^3$, $\alpha=4220 \cdot 10^{-6} \text{ K}^{-1}$, $c=485 \text{ m/s}$, $\sigma=0.007 \text{ N/m}$, $c_p=1610 \text{ J/(kg}\cdot\text{K)}$.
- p) Sodium, $M=0.023 \text{ kg/mol}$, $\rho_L=780 \text{ kg/m}^3$, $\rho_S=970 \text{ kg/m}^3$. The Na-K eutectic alloy, with 22% Na by mass, is a room-temperature liquid, $T_m=-12.6 \text{ }^\circ\text{C}$, $T_b=785 \text{ }^\circ\text{C}$, used in high-temperature high-heat-transfer applications; at 100 $^\circ\text{C}$, $\rho=855 \text{ kg/m}^3$, $\alpha=340 \cdot 10^{-6} \text{ 1/K}$, $c=936 \text{ J/(kg}\cdot\text{K)}$, $k=23 \text{ W/(m}\cdot\text{K)}$, $\mu=505 \cdot 10^{-6} \text{ Pa}\cdot\text{s}$, $\sigma=115 \cdot 10^{-3} \text{ N/m}$ and $\sigma_{\text{elec}}=2.5 \cdot 10^6 \text{ S/m}$, i.e. 4% that of Cu.
- q) Sulfur hexafluoride has no normal points for melting and boiling because at the normal pressure of 100 kPa the only phase change is the solid-gas transition at 209 K (normal sublimation point). Data in this table refers to the triple point: $p_{tr}=226 \text{ kPa}$, $T_{tr}=224 \text{ K}=-49.4 \text{ }^\circ\text{C}$; i.e., $\rho_{l,tr}=1845 \text{ kg/m}^3$, $h_{sv}=h_{sl}+h_{lv}=40+162=202 \text{ kJ/kg}$. Sublimation point data: $T=209 \text{ K}=-63.9 \text{ }^\circ\text{C}$, $\rho_s=2770 \text{ kg/m}^3$, $h_{sv}=202 \text{ kJ/kg}$. Liquid at 288 K and its equilibrium pressure (1.85 MPa) has $\rho_l=1440 \text{ kg/m}^3$, $\alpha=7070 \cdot 10^{-6} \text{ K}^{-1}$, $c=252 \text{ m/s}$, $\sigma=0.003 \text{ N/m}$, and $c_p=1165 \text{ J/(kg}\cdot\text{K)}$. See further data under [Gas properties](#). See additional comments in f).
- r) Tetradecafluorohexane or perfluorohexane (traded as Fluorinert FC-72, or as Flutec PP1), is a liquid coolant commonly used in electronics cooling because of its electrical insulation properties and stability (thermal, chemical, and biological). Its vapour pressure at 25 $^\circ\text{C}$ is 30 kPa. Its refractive index is $n=1.251$. It has zero ozone depletion potential (ODP=0), but a high global warming potential (GWP>5000).
- s) Uranium hexafluoride has no normal points for melting and boiling because at the normal pressure of 100 kPa the only phase change is the solid-gas transition at 329 K (normal sublimation point). Data in this table refers to the triple point: $p_{tr}=152 \text{ kPa}$, $T_{tr}=337 \text{ K}=-64 \text{ }^\circ\text{C}$; i.e., $\rho_{l,tr}=3700 \text{ kg/m}^3$, $h_{sv}=h_{sl}+h_{lv}=54+82=136 \text{ kJ/kg}$. Sublimation point data: $T=329 \text{ K}=56.4 \text{ }^\circ\text{C}$, $\rho_s=4850 \text{ kg/m}^3$, $h_{sv}=136 \text{ kJ/kg}$. See further data under [Gas properties](#). See additional comments in f).
- t) Water properties may be used as a first approximation for many natural aqueous solutions (milk, wine, beer, vinegar, seawater, urine, fruit juices, etc.). Their densities are typically $\rho=1020..1030 \text{ kg/m}^3$, their melting points 1..2 K below that of water, their boiling points 0.5..1.5 K above that of water, their thermal capacities some 80% of water. Pure water has anomalous dilatation in the 0..4 $^\circ\text{C}$ range, with maximum density $\rho=1000 \text{ kg/m}^3$ at $T_4=3.98 \text{ }^\circ\text{C}=277.13 \text{ K}$ decreasing with temperature to 958 kg/m^3 at 100 $^\circ\text{C}$ (with a minimum of 322 kg/m^3 at the critical point); a good approximation in the 0..200 $^\circ\text{C}$ range may be $\rho=1000-0.1 \cdot (T-T_4)-0.0033 \cdot (T-T_4)^2 \text{ kg/m}^3$, with T_4 as above. Interface tension of water/air or water/vapour is 0.073 N/m, but for water/mercury 0.390 N/m, water/octane 0.052 N/m, water/benzene 0.035 N/m. Contact angle water/glass in air 0° if pure, some 30° typical; mercury/glass in air 140° if pure, some 120° typical. Liquid viscosity varies a lot with temperature; e.g. for water, $\mu=1.8 \cdot 10^{-3} \text{ Pa}\cdot\text{s}$ at 0 $^\circ\text{C}$, $0.5 \cdot 10^{-3} \text{ Pa}\cdot\text{s}$ at 50 $^\circ\text{C}$ and $0.35 \cdot 10^{-3} \text{ Pa}\cdot\text{s}$ at 100 $^\circ\text{C}$. The boiling point of water at 100 kPa is $T_b=372.75 \pm 0.02 \text{ K}$ ($99.60 \pm 0.02 \text{ }^\circ\text{C}$), whereas at 101.325 kPa (1 atm) it is $373.12 \pm 0.02 \text{ K}$ ($99.97 \pm 0.02 \text{ }^\circ\text{C}$).
- u) Heavy water usually means water that has been enriched in the deuterium isotope (without changing oxygen isotope composition), in the form HDO or D_2O ; data here only apply to D_2O . Heavy water, contrary to normal (or light) water, does not quench thirst; seeds do not germinate. Additional data: for H_2O (i.e. hydrogen oxide), $\rho_{\text{max}}=1000 \text{ kg/m}^3$ at 3.98 $^\circ\text{C}$ ($\rho_{\text{sol}}=917 \text{ kg/m}^3$ at $T_f=0 \text{ }^\circ\text{C}$); for D_2O (i.e. deuterium oxide): $\rho_{\text{max}}=1106 \text{ kg/m}^3$ at 11.2 $^\circ\text{C}$, $\rho_{\text{sol}}=1018 \text{ kg/m}^3$ at $T_f=3.82 \text{ }^\circ\text{C}$ (thus, a heavy-water ice-cube sinks in normal water); for T_2O (i.e. tritium oxide): $\rho_{\text{max}}=1215 \text{ kg/m}^3$ at 13.4 $^\circ\text{C}$, $\rho_{\text{sol}}=? \text{ kg/m}^3$ at $T_f=4.49 \text{ }^\circ\text{C}$.